

# Alpha Callisto

## Discrete Input Interface-Technical Sheet



## Interfaces with any Alpha LED Display

- Adaptive's Callisto Dry Contact Module interfaces with any Alpha-based Display Unit
- Customized emergency messages can be displayed at the push of a button for an added level of facility Security
- Supports integration with leading fire and security panel manufacturers and network-based Emergency Mass Notification software providers
- Models for Indoor, Semi-Outdoor and Outdoor applications



Manufacturing quality LED display solutions in the United States for over 35 years.

# Alpha Callisto

## Discrete Input Interface- Technical Sheet

### Interface with Adaptive's MNS LED Displays

- 8 contact closures per device
- Each unit can trigger up to eight customized messages
- Up to four devices can be stacked allowing for 32 contact closures and 32 messages



Alpha 4080 RGB MNS Display



Alpha 4120 RGB MNS Display

Weight	12 oz.
Dimensions	1.875"H x 5.875" W x 4" D
Storage Temp. Range	-40 to 85°C
Operating Temp. Range	-20 to 70°C
Humidity	10 to 90% non condensing
Avg. Current Draw	250 mA @5V
Input Voltage	Ac Aadapter 5VDC
Enclosure Mounting	Din Mountable
Connection to Sign	RS485
Inputs per Module	8 Max
Networkable	Up to 4 modules on a network (32 inputs max)

